

| Technical specifications: | | | | | | |
|---------------------------|------------------|------------------|------------------|-------------------------|-------------------------|-------------------------|
| Product: | CS-5 | CS-6 | CS-8 | CST-5 | CST-6 | CST-8 |
| Shape: | round | round | round | round | round | round |
| Speakers: | 13 cm | 16.5 cm | 20 cm | 13 cm + 1.5 cm | 15 cm + 1.5 cm | 20 cm + 1.5 cm |
| Rated power transformer: | 1.25/2.5/5 W RMS | 1.25/2,5/5 W RMS | 2.5/5/10 W RMS | 1.25/2.5/5 W RMS | 1.25/2.5/5 W RMS | 2.5/5/10 W RMS |
| Rated power speaker: | max. 30 W RMS | max. 40 W RMS | max. 60 W RMS | 5/10/20 W RMS | 7.5/15/30 W RMS | 10/20/40 W RMS |
| Sensitivity: | 90 dB (1 W, 1 m) | 90 dB (1 W, 1 m) | 92 dB (1 W, 1 m) | 87 dB, ±3 dB (1 W, 1 m) | 87 dB, ±3 dB (1 W, 1 m) | 87 dB, ±3 dB (1 W, 1 m) |
| Max. SPL (1 m): | | | | 96 dB | 99 dB | 101 dB |
| Impedance: | 8 Ω | 8 Ω | 8 Ω | 8 Ω | 8 Ω | 8 Ω |
| Frequency range: | 100-10,000 Hz | 100-10,000 Hz | 80-18,000 Hz | 100-20,000 Hz | 90-20,000 Hz | 50-20,000 Hz |
| Dimensions: | 192 x 60 mm | 230 x 70 mm | 275 x 85 mm | 203 x 80 mm | 230 x 90 mm | 270 x 105 mm |
| Mounting cutout: | 165 mm ø | 195 mm ø | 235 mm ø | 170 mm ø | 200 mm ø | 240 mm ø |
| Weight: | 0.7 kg | 0.76 kg | 1.2 kg | 1.4 kg | 1.6 kg | 2.2 kg |