

Technical specifications:						
Product:	CSE-5	CSE-6	CSE-8	CSP-6	CSC-4	CSC-6
Input voltage:	100 V	100 V	100 V	100 V	100 V	100 V
Speaker:	13.5 cm	16.5 cm	20 cm	15 cm	10 cm	15 cm
Rated power:	3 W RMS (white), 6 W RMS (red), COM (black)	3 W RMS (white), 6 W RMS (red), COM (black)	5 W RMS (white), 10 W RMS (red), COM (black)	3 W RMS (white), 6 W RMS (red), COM (black)	3 W RMS (white), 6 W RMS (red), COM (black)	3 W RMS (white), 6 W RMS (red), COM (black)
Sensitivity (1 W/ 1 m):	93 dB, ± 3 dB	93 dB, ± 3 dB	93 dB, ± 3 dB	91 dB, ± 3 dB	90 dB, ± 3 dB	92 dB, ± 3 dB
Max. SPL (1 m):	97 dB	97 dB	99 dB	97 dB	94 dB	96 dB
Frequency range:	100-15,000 Hz	100-15,000 Hz	100-15,000 Hz	100 Hz - 17 kHz	150-15,000 Hz	100-18,000 Hz
Dimensions (D x D):	175 x 55 mm	188 x 76 mm	230 x 90 mm	188 x 70 mm	180 x 110 mm	200 x 90 mm
Mounting cutout:	145 mm \emptyset	170 mm \emptyset	200 mm \emptyset	164 mm \emptyset	150 mm \emptyset	185 mm \emptyset
Weight:	500 g	750 g	1 kg	0,5 kg	800 g	900 g