

Technical specifications:						
Product:	CSS-5	CSS-6	CSS-8	CSQ-4	CSQ-5	CSQ-6
Shape:	square	square	square	square	square	square
Speakers:	13 cm + 1.5 cm	16.5 cm + 1.5 cm	20 cm + 2.5 cm	10 cm + 1.5 cm	13 cm + 1.5 cm	15 cm + 1.5 cm
Rated power transformer:	1.25/2.5/5 W RMS	1.25/2.5/5 W RMS	2.5/5/10 W RMS	1.25/2.5/5 W RMS	2.5/5/10 W RMS	2.5/5/10 W RMS
Rated power speaker:	max. 30 W RMS	max. 40 W RMS	max. 60 W RMS	5/10/20 W RMS	7.5/15/30 W RMS	10/20/40 W RMS
Sensitivity:	92 dB (1 W, 1 m)	92 dB (1 W, 1 m)	92 dB (1 W, 1 m)	89 dB, ±3 dB (1 W, 1 m)	89 dB, ±3 dB (1 W, 1 m)	87 dB, ±3 dB (1 W, 1 m)
Impedance:	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω
Frequency range:	100-15.000 Hz	100-15,000 Hz	80-15,000 Hz	90-18.000 Hz	90-18,000 Hz	50-18,000 Hz
Dimensions:	280 x 190 x 60 mm	305 x 220 x 60 mm	373 x 273 x 60 mm	190 x 190 x 80 mm	220 x 220 x 95 mm	255 x 255 x 95 mm
Mounting cutout:	243 x 155 mm	270 x 185 mm	326 x 226 mm	145 x 145 mm	190 x 190 mm	225 x 225 mm
Weight:	1.2 kg	1.5 kg	2 kg	1.3 kg	1.7 kg	2.2 kg