

Technical specifications:							
Product:	WP-1H	WP-5H	WP-10H	WP-10W	WP-15W	WP-20W	WP-25W
Speakers:	20 cm	13 cm	15 cm	13 cm	16.5 cm	13 cm	16.5 cm
Rated power transformer:	5/10/20 W RMS	10 W RMS	7.5/15/30 W RMS	2.5/5/10 W RMS	5/10/20 W RMS	2.5/5/10 W RMS	5/10/20 W RMS
Rated power speaker:	5/10/20 W RMS		7.5/15/30 W RMS	2.5/5/10 W RMS	5/10/20 W RMS	2.5/5/10 W RMS	5/10/20 W RMS
Sensitivity (1 W/1 m):	92 dB, ± 3 dB	90 dB, ± 3 dB	92 dB, ± 3 dB	91 dB, ± 3 dB	92 dB, ± 3 dB	91 dB, ± 3 dB	92 dB, ± 3 dB
Max. SPL (1 m):				100 dB	101 dB	100 dB	104 dB
Impedance:	500/1000/2000 Ω		8 Ω	8 Ω	8 Ω	8 Ω	8 Ω
Frequency range:	130-15,000 Hz	150-15,000 Hz	110-18,000 Hz	130-15,000 Hz	100-15,000 Hz	130-15,000 Hz	110-15,000 Hz
Dimensions (D x D):	254 x 230 mm	180 x 130 mm	378 x 302 mm	138 x 205 mm	170 x 248 mm	138 x 205 mm	170 x 252 mm
Weight:	2.2 kg	1.2 kg	2.5 kg	1.5 kg	1.7 kg	2.1 kg	2.8 kg