

EUROLITE VLS-1200RGB 40k Showlaser

No. 51741465

- + RGB high-power laser (laser diode: 635 nm red, 532 nm green, 450 nm blue)
- + Effects: layers, grids, tunnels, waves, writing, graphics, animation
- + Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- + Delivery in flightcase
- + Operation: ILDA, DMX512, auto, sound-active
- + Modulation: analog for more brilliant color changes
- + Laser with the classification 4



NEW

DMX

ILDA

- Laser with the classification 4
- Modulation: analog for more brilliant color changes
- RGB-color-mixture
- Operation: ILDA, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- Laser diode: 635 nm red, 532 nm green, 450 nm blue
- For DMX-operation on the rear panel: X and Y size adjustment
- Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- Delivery in flightcase
- Read user manual before use. Laser installation, alignment and operation only by qualified and trained personell! Never open the housing!



Technical specifications:

Power supply:	230 VAC, 50 Hz ~
Power consumption:	70 W
DMX control channels:	13
DMX512 connection:	3-pin XLR
ILDA-connection:	25-pin SUB-D
Maximum optical power:	1200 mW
Laser classification:	4
Wavelength:	650/532/450 nm
Laser-modules:	Red 500 mW, green 300 mW, blue 400 mW
Beam:	5 mm @ output
Scanning speed:	40000 pps @ 8°
Dimensions without bracket (LxWxH):	515 x 350 x 205 mm
Weight:	12 kg

Accessories:

EUROLITE NOT-20 Laser interlock	No. 51741490
ILDA cable 20m	No. 51741495
EUROLITE HE Laser software	No. 51885500
EUROLITE Laser interface	No. 51885505
Pangolin QuickShow 2.0 FB3/QS	No. 51885510
Saveking Safety bond 3x1000 silver	No. 58010254

