

## Motor projection screen IR

**No. 80901175** ..... IR 4:3  
**No. 80901177** ..... IR 4:3  
**No. 80901179** ..... IR 4:3  
**No. 80901185** ..... IR 16:9  
**No. 80901187** ..... IR 16:9  
**No. 80901189** ..... IR 16:9

+ Operation via low-noise motor with remote-control  
 + Motorized Wall Screen for XXL entertainment  
 + Suitable for all LCD-beamers and DLP-beamers

• Motorized Wall Screen for XXL entertainment • Projection screen in 4:3/16:9 aspect ratio • Gain-factor of 1.0 for universal use • Screen type D (diffuse) for even light reflection • Matt, white canvas for genuine projections • Bar-tensioned canvas to keep the fabric flat and immobile • With surrounding black border top, bottom, right and left • Suitable for all LCD-beamers and DLP-beamers • Impervious to light due to black back • White steel-sheet housing in a modern look • Operation via low-noise motor • Stepless height adjustment with automatic endstop • Controlled via switch or infrared remote-control • For wall or ceiling mounting • Ready for connection with power plug - no electrician needed! • For home cinema, party room etc.



Technical specifications:						
Product:	80901175	80901177	80901179	80901185	80901187	80901189
Power supply:	230 VAC, 50 Hz~	230 VAC, 50 Hz~	230 VAC, 50 Hz~	230 VAC, 50 Hz~	230 VAC, 50 Hz~	230 VAC, 50 Hz~
Power consumption:	25 W	40 W	75 W	25 W	40 W	75 W
Type:	Stationary electric screen D	Stationary electric screen D	Stationary electric screen D	Stationary electric screen D	Stationary electric screen D	Stationary electric screen D
Projection format:	4:3	4:3	4:3	16:9	16:9	16:9
Projection type:	Front projection	Front projection	Front projection	Front projection	Front projection	Front projection
Projection size:	3 m	3.75 m	4.5 m	2.75 m	3.5 m	4 m
Projection area:	240 x 180 cm	300 x 220 cm	360 x 270 cm	240 x 135 cm	300 x 168 cm	360 x 200 cm
Surrounding border:	4 cm	4 cm	4 cm	4 cm	4 cm	4 cm
Gain:	1.0	1.0	1.0	1.0	1.0	1.0
Viewing angle:	100°	100°	100°	100°	100°	100°
Base material:	PVC	PVC	PVC	PVC	PVC	PVC
Screen surface:	Matt, white	Matt, white	Matt, white	Matt, white	Matt, white	Matt, white
Thickness:	0.4 mm	0.4 mm	0.4 mm	0.4 mm	0.4 mm	0.4 mm
Roll up/down time:	50 s	50 s	50 s	50 s	50 s	50 s
Remote-control:	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared
Frequency range:	315 THz	315 THz	315 THz	315 THz	315 THz	315 THz
Coverage:	approx. 50-100 m (with line-of-sight)	approx. 50-100 m (with line-of-sight)	approx. 50-100 m (with line-of-sight)	approx. 50-100 m (with line-of-sight)	approx. 50-100 m (with line-of-sight)	approx. 50-100 m (with line-of-sight)
Battery:	1 x 23AE 12V	1 x 23AE 12V	1 x 23AE 12V	1 x 23AE 12V	1 x 23AE 12V	1 x 23AE 12V
Dimensions:	2730 x 95 x 85 mm	3500 x 90 x 90 mm	4010 x 120 x 130 mm	2730 x 95 x 85 mm	3350 x 90 x 90 mm	4010 x 120 x 130 mm
Weight:	12 kg	17 kg	22 kg	13 kg	14.5 kg	23.5 kg